

# MAXIMA 5W-40

Fully Synthetic Motor Oil

## Description

Fully synthetic multi-grade engine oil which is blended from a combination of high-tech base oil and high performance additives.

## Applications

Suitable for all diesel engines in the passenger cars and light commercial vehicles demanding SAE 5W-40 viscosity grade and ACEA A3/B4 engine oil performance level.

## Benefits

- Provides maximum fuel economy, keeps engine clean.
- Extends oil change interval.
- Provides best fuel efficiency and increases engine efficiency.
- Contributes to high motor performance by reducing friction.
- Provides excellent oxidation resistance.

## Performance

API SN/CF, ACEA A3/B4, Fiat 9.55535-N2, MB-Approval 226.5/229.5, Renault RN 0700/RN 0710, VW 502.00/505.00

## Typical Specifications\*

SAE Viscosity Grade		5W-40
Density, 15 °C, kg/liter	ASTM D4052	0,854
Flash Point, COC, °C	ASTM D92	232
Viscosity, 40 °C, mm <sup>2</sup> /s	ASTM D445	77
Viscosity, 100 °C, mm <sup>2</sup> /s		12,80
Viscosity Index	ASTM D2270	169
Pour Point, °C	ASTM D97	-36

\* Values shown may differ between productions.

