

MAXIMA PG 0W-30

Fully Synthetic Motor Oil for New Generation PSA Group Vehicles

Description

Maxima PG 0W-30, an engine oil formulated with the synthetic base oils and special additives, produced for especially PSA Group Vehicles with emission reducing systems that equipped with DPF and SCR.

Applications

Suitable for PSA Group Vehicles with "BlueHDI" technology engine containing SCR. Also suitable for gasoline and diesel engines of PSA Group Vehicles with or without DPF. Maxima PG 0W-30 can be used in vehicle engines that require ACEA C3 performance level.

Benefits

- Extends the life of aftertreatment systems.
- Provides longer engine life with high anti-wear properties.
- Excellent lubrication even at low temperatures.
- Contribution to the fuel economy by reducing friction.
- Helps protect the environment by reducing emissions.
- Reduces sludge and deposits by excellent oxidation resistance.

Performance

PSA B71 2312, FIAT 9.55535-DS1, ACEA C2-12

Typical Specifications*

SAE Viscosity Grade		0W-30
Density, @ 15 °C, kg/m ³	ASTM D-4052	0,840
Flash Point, COC, °C	ASTM D-92	240
Viscosity, 40 °C, mm ² /s	ASTM D 445	54,40
Viscosity, 100 °C, mm ² /s		9,9
Viscosity Index	ASTM D-2270	165
Pour Point, °C	ASTM D- 97	-48

* Values shown may differ between productions.