

# MAXIMUS 10W-30

Synthetic Diesel Engine Oil

## Description

Synthetic diesel engine oil specially formulated with premium quality synthetic base oils and new generation performance additives to ensure excellent lubricating of new generation diesel engines operating under severe conditions.

## Applications

Recommended for all applications involving light commercial vehicles, trucks, buses, construction machines and generators equipped with a diesel engine, especially with turbocharged and low emission diesel engines.

## Benefits

- Maximizes engine performance and reduces maintenance cost by preventing excess wear.
- Contributes to fuel efficiency by reducing friction.
- Provides protection in wide range of temperature.
- Prevents sludge and cleans engine.

## Performance

API CI-4, ACEA E7-16, MAN M3275, MB 228.3, VOLVO VDS-3, RENAULT RLD-2, CUMMINS 20077/20078, MACK EO-N/M, Global DHD1, CAT ECF-1a, JASO DH-1, DETROIT DIESEL DDC 93K215, FORD WSS-M2C921-A

## Typical Specifications\*

SAE Viscosity Grade		10W-30
Density, @ 15 °C, kg/m <sup>3</sup>	ASTM D-4052	0,873
Flash Point, COC, °C	ASTM D-92	230
Viscosity, 40 °C, mm <sup>2</sup> /s	ASTM D-445	80
Viscosity, 100 °C, mm <sup>2</sup> /s		11,8
Viscosity Index	ASTM D-2270	141
Pour Point, °C	ASTM D- 97	-33

\* Values shown may differ between productions.

