

MAXIMUS 10W-40

Synthetic Heavy Duty Diesel Engine Oil

Description

Synthetic diesel engine oil, meeting UHPD (Ultra High Performance Diesel) requirements, formulated with high-tech additives and synthetic base oils.

Applications

It is recommended for all 4-cycle light commercial or heavy-duty diesel engines with or without turbocharger those are working in construction, mining, transportation, agriculture and fleet.

Benefits

- Provides long service life and reduces oil consumption.
- Protects the engine against wear at high temperatures by its excellent thermal stability.
- Provides fuel saving.
- Preserves the engine against rusting and corrosion.

Performance

API CI-4, ACEA E4/E7-16, MB-Approval 228.5 MAN M3277, Volvo VDS-3, CUMMINS 20076/77/78, MACK E0-N, Renault RLD-2, DETROIT DIESEL DDC93K215, DEUTZ DQC III-10, JASO DH-1, Global DHD-1, MTU Type 3

Typical Specifications*

SAE Viscosity Grade		10W-40
Density, @ 15 °C, kg/m ³	ASTM D-4052	0,869
Flash Point, COC, °C	ASTM D-92	230
Viscosity, 40 °C, mm ² /s	ASTM D-445	93
Viscosity, 100 °C, mm ² /s		13,5
Viscosity Index	ASTM D-2270	146
Pour Point, °C	ASTM D- 97	-36

* Values shown may differ between productions.