

## MAXIMUS HD 10W-40

Ultra High Performance Diesel Engine Oil

### Description

Engine oil formulated with advanced technology additives and premium quality synthetic base oils, developed for Euro 5 and Euro 6 vehicles.

### Applications

It is recommended for all heavy duty vehicles, construction equipment and highway fleet equipped with high power, 4-cycle diesel engines. It is convenient for engines with and without DPF and engines with EGR and SCR. It is especially recommended for modern Volvo Heavy Duty engines.

### Benefits

- Protects the engine and particle filter by preventing excess friction and corrosion with its low-ash formulation.
- Reduces fuel consumption and extends drain intervals.
- Achieves piston cleanliness by reducing piston deposit and residue.
- Protects the environment by exhaust emission control.

### Performance

API CJ-4/SN, ACEA E9-12, MB-Approval 228.31, VOLVO VDS-4, RENAULT TRUCKS RLD-3, MAN M3575, CUMMINS 20081, MTU Type 2.1, MACK EO-0 PREMIUM PLUS, CATERPILLAR ECF-3/ECF-2/ECF-1-a, DEUTZ DQC III-10LA, DETROIT DIESEL DDC93K218

### Typical Specifications\*

SAE Viscosity Grade		10W-40
Density, @ 15 °C, kg/m <sup>3</sup>	ASTM D-4052	0,858
Flash Point, COC, °C	ASTM D-92	220
Viscosity, 40 °C, mm <sup>2</sup> /s	ASTM D-445	91,5
Viscosity, 100 °C, mm <sup>2</sup> /s		13,9
Viscosity Index	ASTM D-2270	153
Pour Point, °C	ASTM D- 97	-42

\* Values shown may differ between productions.