

# MAXIMUS TURBO DIESEL EXTRA 15W-40

Heavy Duty Diesel Engine Oil

## Description

Long life diesel engine oil, equivalent to super high performance diesel (SHPD) engine oil providing excellent performance in diesel engines operating with low and high sulfur fuels.

## Applications

It is recommended for all heavy-duty vehicles, buses, trucks, construction equipment, and generators having diesel engines, especially turbocharged and low-emission diesel engines.

## Benefits

- Prevents the engine using fuel with high sulfur content by its high TBN value.
- Reduces wear at high speeds and temperatures.
- Increases combustion efficiency by keeping engine clean.
- Extends spare parts life.

## Performance

API CI-4, ACEA E7-16, MB-Approval 228.3, JASO DH-1, GLOBAL DHD-1, MTU Type 2, Volvo VDS-3 RENAULT RV-I/RLD-2, MACK EO-N, CUMMINS CES 20077/78, DETROIT DIESEL DDC 93K215, DEUTZ DQC-III, MAN M3275, CAT ECF-1a

## Typical Specifications\*

SAE Viscosity Grade		15W-40
Density, @ 15 °C, kg/m <sup>3</sup>	ASTM D-4052	0,886
Flash Point, COC, °C	ASTM D-92	240
Viscosity, 40 °C, mm <sup>2</sup> /s	ASTM D-445	114
Viscosity, 100 °C, mm <sup>2</sup> /s		15
Viscosity Index	ASTM D-2270	139
Pour Point, °C	ASTM D- 97	-30

\* Values shown may differ between productions.