

ÖZEL ANTİFRİZ

Ethylene Glycol Based Special Antifreeze

Description

It is a high quality coolant antifreeze with long service life, containing special additives in the ethylene base substance. It does not contain nitrites, amine and phosphate.

Applications

It can be used in all cooling systems especially new generation vehicles.

Benefits

- Provides perfect protection of the engine cooling system against freezing, boiling, corrosion, rusting, cavitation and wearing out.
- It does not evaporate at radiator temperatures.
- For perfect performance, the cooling system should not be contaminated and there should be no leak.
- Only clean and clear water should be used.
- It might be added into the cooling system that contains ethylene based antifreeze.

Performance

SAE J 1034, TS 3582, MAN 324 Type NF, MB 325.0, ZF Intarder, BMW N 600 69.0, AUDI TL 774-C, PORSCHE 774 C, VW TL 774 C, CAT SEBU 6250-12, MTU MTL 5048, JENBACHER, SKODA, SEAT, OPEL.

Typical Specifications*

Density, @ 15°C, kg/m ³	ASTM D-4052	1,129
Freezing Point, °C, (%50 Antifreeze)	ASTM D-1177	-38
Freezing Point, °C, (%33 Antifreeze)		-18
Boiling Point, °C, (%100)	ASTM D-1120	174
Ph, 20°C, (%100)	ASTM D-1287	7.2
Ph, 20°C, (%30)		8.4

* Values shown may differ between productions.



Petrol Ofisi