

# SUPERŞARJ SERIES

## Monograde High Quality Diesel Engine Oils

### Description

Mono grade high viscosity index engine oil produced with high quality base oils and additives.

### Applications

Can be used in heavy duty vehicles.

### Benefits

- Thanks to a high level of TBN, protects the engine against rust, corrosion and wear when using high sulphur content fuel.
- Minimizes the deposit under severe conditions, prevents friction.
- Keeps fluidity at low temperatures due to its high viscosity index.
- Increases combustion efficiency by keeping the engine clean.

### Performance

API CF/CF-4/SG, MIL-L-2104D ALLISON C3, CAT T0-2

### Typical Specifications\*

SAE Viscosity Grade		10W	30	30 (20 TBN)	40	50
Density, @ 15 °C, kg/m <sup>3</sup>	ASTM D-4052	0,886	0,890	0,902	0,900	0,899
Flash Point, COC, °C	ASTM D-92	220	240	260	260	270
Viscosity, 40 °C, mm <sup>2</sup> /s	ASTM D-445	39,8	81	94	125	223
Viscosity, 100 °C, mm <sup>2</sup> /s		6	9,8	11	13	19,5
Viscosity Index	ASTM D-2270	107	100	102	98	99
Pour Point, °C	ASTM D- 97	-30	-18	-18	-15	-12

\* Values shown may differ between productions.



**Petrol Ofisi**